

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
6 March 2003 (06.03.2003)


PCT

(10) International Publication Number
WO 03/018362 A1

- (51) International Patent Classification⁷: B60R 1/00, 11/02, 7/04
- (21) International Application Number: PCT/US02/26722
- (22) International Filing Date: 22 August 2002 (22.08.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/314,723 24 August 2001 (24.08.2001) US
- (71) Applicant: BLUE RIDGE INTERNATIONAL PRODUCTS COMPANY [US/US]; 225 Blue Ridge Parkway, P.O. Box 989, Freeport, FL 32439 (US).
- (72) Inventors: DARLING, Sandra, M.; 216 Windward Cove Road, East, Niceville, FL 32578 (US). KANE, Michael, T.; 5848 East Lake Road, Conesus, NY 14435 (US).
- (74) Agents: SCHNEDLER, Steven C. et al.; Carter & Schnedler, P.A., 56 Central Avenue, Suite 101, P.O. Box 2985, Asheville, NC 28802 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: PANEL ATTACHMENT SYSTEM




(57) Abstract: A viewing panel device (50), such as a mirror device (50) used inside a motor vehicle (20) for observing an infant (38) in a rear-facing child safety seat (34) secured to the rear seat (24) of the vehicle (20). The viewing panel device (50) may be employed in a plurality of attachment configurations, for use with a plurality of possible vehicle configurations. In one configuration, the top tether anchorage point (110) included in newer vehicles as part of the LATCH anchorage point system is employed.



WO 03/018362 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



15

THIS PAGE BLANK (USPTO)








FIG. 2

THIS PAGE BLANK (USPTO)





THIS PAGE BLANK (USPTO)



THIS PAGE BLANK (11/27/70)

THIS PAGE BLANK (USPTO)



THIS PAGE BLANK (USPTO)

PANEL ATTACHMENT SYSTEM

Technical Field

5 The invention relates to attachment systems for panels attached to seats of vehicles, such as but not limited to mirrors used inside a motor vehicle for observing an infant in a rear-facing child safety seat secured to the rear seat of the vehicle.

Background Art

10 Mirror devices used inside a motor vehicle for observing an infant in a rear-facing child safety seat secured to the rear seat of the vehicle are disclosed, for example, in the following U.S. patents: Cossey No. 4,702,572; Masucci No. 4,712,892; Erickson No. 4,733,956;
15 Harris No. 4,902,118; Gardner No. 4,909,618; Lumbra et al No. 5,103,347; Nolan-Brown No. 5,285,321; Rubin No. 5,576,898; Sorenson No. 6,039,455; Brennan et al No. 6,120,155; Mercado No. 6,305,810 and Monahan et al No. 6,354,708.

20 Very briefly, in such devices, a mirror is mounted near the top of the rear seat of a motor vehicle in such a way that the driver of the vehicle, by looking in the conventional rear view mirror, can observe in the mirror mounted near the top of the rear seat an infant in
25 a child safety seat of the type in which the infant is positioned facing the rear of the vehicle. A variety of attachment methods for such mirror devices have been proposed and employed.

Disclosure of the Invention

30 In one aspect, the invention is embodied in a viewing panel device having a plurality of attachment configurations for use in vehicles including a relatively rearwardly-positioned vehicle seat with a seat back having a top surface, and of a plurality of possible

vehicle configurations including in vehicles having a top tether anchorage point intended for attachment of the top tether of a forward-facing child safety seat, and in vehicles having a headrest positioned over the vehicle seat back. The device includes a generally vertical viewing panel having a front viewing surface and a rear surface. A bottom panel is connected to the viewing panel generally on the rear surface and on a lower portion thereof. The bottom panel has a top surface and a bottom surface that contacts the seat back top surface. A fastener element is connected to the viewing panel on an upper portion thereof. A diagonal support element can extend between the viewing panel rear surface and the bottom panel top surface, and is removably attachable at one end. A tether strap extends from the bottom panel and terminates in a fastener that can be attached either to the top tether anchorage point in a vehicle so configured, or to the fastener element when the tether strap is looped around the headrest in a vehicle so configured.

In another aspect, the invention is embodied in a viewing panel device for use in a vehicle including a relatively rearwardly-positioned vehicle seat with a seat back having a top surface, and including a top tether anchorage point intended for attachment of the top tether of a forward-facing child safety seat. The device includes a generally vertical viewing panel having a front viewing surface and a rear surface. A support structure is connected to the viewing panel generally on the rear surface thereof. The support structure includes a portion that contacts the seat back top surface. A tether strap extends from the support structure and terminates in a fastener that attaches to the top tether anchorage point.

In yet another aspect, the invention is embodied in a viewing panel device for use in a vehicle including a relatively rearwardly-positioned vehicle seat

with a seat back having a top surface and a headrest positioned thereover. The device includes a generally vertical viewing panel having a front viewing surface and a rear surface. A bottom panel is connected to the
5 viewing panel generally on the rear surface and on a lower portion thereof. The bottom panel has a bottom surface that contacts the seat back top surface. A fastener element is connected to the viewing panel on an upper portion thereof. A tether strap extends from the
10 bottom panel and terminates in a fastener that attaches to the fastener element when the tether strap is looped around the headrest.

In still another aspect, the invention is embodied in a viewing panel device for use in a vehicle
15 including a rear vehicle seat with a seat back having a top surface, and a rear shelf behind the seat back. The device includes a generally vertical viewing panel having a front viewing surface and a rear surface. A support structure is connected to the viewing panel generally on
20 the rear surface thereof. The support structure includes a portion that contacts the seat back top surface. A tail extends from the support structure and is tucked in between the vehicle seat back and the rear shelf for frictional engagement.

25 In another aspect, the invention is embodied in a viewing panel device for use in a vehicle including a relatively rearwardly-positioned vehicle seat with a seat back having a top surface and a rear surface. The device includes a generally viewing panel having a front viewing
30 surface and a rear surface. A support structure is connected to the viewing panel generally on the rear surface thereof. The support structure includes a portion that contacts the seat back top surface, and has an extending tail. The extending tail has a fastener
35 element on the underside thereof for removably fastening to the vehicle seat rear surface.

Brief Description Of The Drawings

FIG. 1 is a diagrammatic illustration of a vehicle including a mirror device for observing an infant in a rear-facing child safety seat secured to the rear seat of the vehicle;

FIG. 2 is a three-dimensional view of a viewing panel device embodying the invention in the exemplary form of a mirror device, for use with a plurality of possible vehicle configurations, and correspondingly capable of being employed in several attachment configurations;

FIG. 3 is a side elevational view depicting the mirror device of FIG. 2 employed in a first attachment configuration, referred to herein as a "Tether Attachment" configuration;

FIG. 4 is an enlarged three-dimensional view of a portion of FIG. 3, depicting attachment to the top tether anchorage point of a LATCH anchorage point system;

FIG. 5 is a side elevational view depicting the mirror device of FIG. 2 employed in a second attachment configuration, referred to herein as a "Headrest Attachment" configuration;

FIG. 6 is a three-dimensional view, generally from the rear, of the mirror device employed in the "Headrest Attachment" configuration of FIG. 5;

FIG. 7 is a side elevational view of the mirror device of FIG. 2 employed in a third attachment configuration, referred to herein as a "Tuck Attachment" configuration;

FIG. 8 is a three-dimensional view, generally from the rear, of the mirror device employed in the "Tuck Attachment" configuration of FIG. 7;

FIG. 9 is a side elevational view of the mirror device of FIG. 2 employed in a fourth attachment configuration, referred to herein as a "Fastener Attachment" configuration; and

FIG. 10 is a three-dimensional view, generally from the rear, of the mirror device employed in the "Fastener Attachment" configuration of FIG. 9.

Best Mode for Carrying Out Invention

5 Referring first to FIG. 1, represented is a vehicle 20 in the form of an automobile 20 including a front vehicle seat 22 and a rearwardly-positioned vehicle seat 24. In FIG. 1 the seat 24 is the rear vehicle seat, since there are only front and rear seats and no
10 intermediate seats in the particular vehicle 20 of FIG. 1.

The rear vehicle seat 24 has a seat back 26 with a top surface 28. Behind the seat back 26, and extending up to a rear window (not shown), is a rear
15 shelf 32, which also may be referred to as a rear filler panel 32.

On and secured to the rear vehicle seat 24 is a rear-facing child safety seat 34 secured by a seatbelt assembly 36 in conventional manner. An infant 38 is
20 seated in the child safety seat 34.

In the front vehicle seat 24 is a driver 40, who may wish to observe the infant 38. A conventional rear view mirror 42 is attached to the vehicle front windshield 44, but this rear view mirror 42 alone is not
25 sufficient for observing the infant 38, since the infant 38 is facing the rear.

Accordingly, and as noted hereinabove, a variety of mirror devices have been proposed, generally in the form of a mirror mounted in some manner near the
30 top of the rear seat 24 in such a way that the driver 40 can observe the infant 38 by looking in the rear view mirror 42.

A mirror device of this general type and embodying the invention is designated 50. In FIG. 1, the
35 mirror device 50 is shown by way of example in one of its several possible attachment configurations, in particular

the "Tether Attachment" configuration described hereinbelow in detail with reference to FIGS. 3 and 4. The mirror device 50 includes a reflective front surface 52 comprising a non-glass (for safety reasons) mirror 52. 5 As indicated by an optical axis 54, the mirror device 50 enables observation of the infant 38 in the rear-facing child safety seat 34.

FIG. 2 shows the mirror device 50 embodying the invention in isolation and in greater detail. Although 10 the device 50 is shown in FIG. 1 as a mirror device positionable for viewing the infant 38 in the rear-facing child safety seat 34, such is representative of a viewing panel device 50 in general, which may or may not include a mirror. For example, a viewing panel device 50 15 embodying the invention may include ornamentation, fixed, removable, or both, for entertaining the infant 38. Or the viewing panel device 50 may comprise an educational activity panel.

A feature of the viewing panel device 50 is 20 that it embodies a plurality of attachment methods or configurations and can be used in vehicles of various possible vehicle configurations. Thus described hereinbelow with reference to FIGS. 3 and 4 is the manner in which the device 50 is attached in the "Tether 25 Attachment" configuration advantageously employing the upper tether anchorage point of a LATCH anchorage point system. Described hereinbelow with reference to FIGS. 5 and 6 is the manner in which the device 50 is installed in the "Headrest Attachment" configuration. Described 30 hereinbelow with reference to FIGS. 7 and 8 is the manner in which the device 50 is installed in the "Tuck Attachment" configuration. Described hereinbelow with reference to FIGS. 9 and 10 is the manner in which the device 50 is installed in the "Fastener Attachment" 35 configuration.

Referring now particularly to FIG. 2, the viewing panel device 50 includes a relatively rigid

mirror and backing assembly 60 including the reflective front surface 52, that is, the mirror 52, and a fabric rear surface 64, surrounding a core of polyurethane foam (not shown). The mirror and backing assembly 60 thus is
5 representative of a viewing panel 60, which may or may not include a mirror. The mirror and backing assembly 60 or viewing panel 60 is generally vertical during use, although not exactly so, since the mirror 52 is positioned at an appropriate angle for viewing the infant
10 along the optical axis 54 as is diagrammed in FIG. 1. A bottom panel 66 is attached to the mirror and backing assembly 60 generally on the rear surface 64 on a lower portion 68 thereof. The bottom panel 66 has a top surface 70 and a bottom surface 72. Preferably, the
15 bottom surface 72 comprises an anti-skid fabric, such as a rubberized fabric, stitched or otherwise attached to the remainder of the bottom panel 66. During use, the anti-skid bottom surface 72 contacts the seat back top surface 28.

20 The viewing panel device 50 additionally includes a diagonal support element 74 that can extend between the viewing panel rear surface 64 at an upper end 76 of the support element 74 and the top surface 70 of the bottom panel 66 at a lower end 78 of the support
25 element 74. The support element 74 is employed in the "Tether Attachment" configuration of FIGS. 3 and 4, in the "Tuck Attachment" configuration of FIGS. 7 and 8 and in the "Fastener Attachment" configuration of FIGS. 9 and 10, each described hereinbelow. The support element 74
30 is removably attachable to one of the viewing panel 60 rear surface 64 and the bottom panel 66 top surface 70. The bottom panel 66 and the diagonal support element 74 together comprise a support structure 86 connected to the mirror and backing assembly 60 or viewing panel 60.

35 In the illustrated embodiment, the diagonal support element 74 more particularly has its upper end 76 hingedly attached to the rear surface 64 on an upper

portion 82 thereof, and is accordingly permanently attached on the upper portion 82 of the rear surface 64 of the mirror and backing assembly 60. The support element 74 extends diagonally during use between the upper portion 82 and the top surface 70 of the bottom panel 66. The support element 74 at its lower end 78 has a flap 84. Secured to the underside of the flap 84 is a strip 86 of an element of a hook-and-loop fastener system (e.g. Velcro®), in particular the "hook" element 86. The top surface 70 of the bottom panel 66 is of a fabric pile material and serves as the "loop" element of the hook-and-loop fastener system at substantially any point along the top surface 70. The support element 74 generally comprises fabric surrounding a core of a soft plastic material such as plastic regrind, and is sufficiently stiff to provide structural integrity.

Also attached or connected to the mirror and backing assembly 60 or viewing panel 60 on the upper portion 78 of the rear surface 64 is a fastener element 88 in the form of a D-ring 88. The D-ring 88 is employed during use of the mirror device 50 or viewing panel device 50 in the "Headrest Attachment" configuration of FIGS. 5 and 6, described hereinbelow.

Attached to and extending rearwardly from the bottom panel 66 of the support structure 86 is a tether strap 90. At its free or distal end 92 the tether strap 90 terminates in a length-adjustment buckle 94 and a fastener 96 in the form of a J-Hook 96. The tether strap 90 and J-Hook 96 are employed during use of the mirror device 50 or viewing panel device 50 in the "Tether Attachment" configuration of FIGS. 3 and 4 and in the "Headrest Attachment" configuration of FIGS. 5 and 6, each described hereinbelow.

The bottom panel 66 also has an extending tail 98. At the distal end 100 of the extending tail, on the underside thereof, is a strip 102 of an element 102 of a hook-and-loop fastener system (e.g. Velcro®), such as the

"hook" element 102. The extending tail 98 is employed during use of the mirror device 50 or viewing panel device 50 in the "Tuck Attachment" configuration of FIGS. 7 and 8, described hereinbelow. The extending tail 98 and the "hook" element 102 are employed during use of the mirror device 50 or viewing panel device 50 in the "Fastener Attachment" configuration of FIGS. 9 and 10, described hereinbelow.

FIGS. 3 and 4 more particularly illustrate the mirror device 50 or, more generally, the viewing panel device 50, in the first attachment configuration referred to herein as the "Tether Attachment" configuration. The attachment configuration of FIGS. 3 and 4 employs a top tether anchorage point 110 included in newer automobiles, as mandated by United States federal regulation, in particular, through the National Highway Traffic Administration (NHTSA), as part of the so-called LATCH anchorage point system (Lower Anchors and Tethers for CHildren). The LATCH anchorage points are intended for use in combination with forward-facing child safety car seats. When the LATCH anchorage points are employed, the vehicle seat belt system is not required for the installation of a forward-facing child safety car seat. Such forward-facing child safety car seats can have a tether at their upper end, which cooperates with the top tether anchorage point 110. However, in the case of a rear facing infant car seat, the top tether anchorage point 110 is not generally used in combination with the infant car seat, and accordingly is available for other uses. In the particular vehicle configuration represented in FIGS. 3 and 4, the top tether anchorage point 110 is located on the vehicle rear shelf 32 or rear filler panel 32.

In the "Tether Attachment" configuration of FIGS. 3 and 4, the bottom panel 66 is placed over the top surface 28 of the rear seat 24 of the vehicle 20, and the J-hook 96 is attached to the top tether anchorage point

110. In the "Tether Attachment" configuration of FIGS. 3 and 4, the D-ring 88 is not employed, nor is the extending tail 98. The buckle 94 and the support structure 80, more particularly the support element 74 thereof, are adjusted so that the mirror device 50 is in an appropriate position, and the mirror and backing assembly 60 is at a suitable angle for viewing the infant 38 along the optional axis 54 as is diagrammed in FIG. 1.

FIGS. 5 and 6 more particularly illustrate the mirror device 50 or, more generally, the viewing panel device 50, in the second attachment configuration, referred to herein as the "Headrest Attachment" configuration. In the attachment configuration of FIGS. 5 and 6, the mirror device 50 is employed in combination with a rearwardly-positioned vehicle seat 120 which may or may not be the rearmost seat in the vehicle. The seat 120 includes a seat back 122 having a top surface 124. In addition, the seat 120 has a headrest 126 positioned over the top surface 124. The "Headrest Attachment" configuration may be employed in an older vehicle that is not equipped with the LATCH system. The bottom panel 66 is positioned over the top surface 124 of the seat back 122, between the top surface 124 and the headrest 126. The tether strap 90 is looped behind the headrest 126, and the J-hook 96 is attached to the D-ring 88. The effective length of the tether strap 90 is adjusted by means of the adjustment buckle 94 so that the mirror and backing assembly 12 is at a proper angle for viewing the infant 38 along the optical axis 52 as is diagrammed in FIG. 1. In the "Headrest Attachment" configuration of FIGS. 5 and 6, the support element 74 is not employed, and can either lie on top of the headrest 126 as illustrated, or hang generally adjacent the rear surface 64 of the mirror and backing assembly 60. The D-ring 88 and extending tail 98 are not employed either.

FIGS. 7 and 8 more particularly illustrate the mirror device 50 or, more generally, the viewing panel

device 50, in the third attachment configuration, referred to herein as the "Tuck Attachment" configuration. The "Tuck Attachment" configuration likewise may be employed in an older vehicle which is not
5 equipped with the LATCH system, and which accordingly does not have a top tether anchorage point on the rear shelf 32. In this configuration, the extending tail 98 of the bottom panel 66 is folded and tucked in between the vehicle seat back 26 and the rear shelf 32, and held
10 by friction, aided by the anti skid fabric on the bottom surface 72 of the bottom panel 66. The support structure 80, more particularly the support element 74 thereof, is adjusted, in combination with the particular point at which the fabric of the extending tail 98 is tucked in
15 between the vehicle seat back 26 and rear shelf 32, so that the mirror and backing assembly 60 is positioned at an appropriate angle for viewing the infant 38 along the optical axis 54 as is diagrammed in FIG. 1. In the "Tuck Attachment" configuration of FIGS. 7 and 8, the D-ring 88 and the tether strap 90 with its J-hook are not employed.
20

Finally, FIGS. 9 and 10 more particularly illustrate the mirror device 50 or, more generally, the viewing panel device 50, in the fourth attachment configuration, referred to herein as the "Fastener
25 Attachment" configuration. In the attachment configuration of FIGS. 9 and 10, the mirror device 50 is employed in combination with a rearwardly-positioned vehicle seat 130 which may or may not be the rearmost seat in the vehicle. The seat 130 includes a seat back
30 132 having a top surface 124, as well as an accessible rear surface 136. The "Fastener Attachment" configuration likewise may be employed in an older vehicle that is not equipped with the LATCH system.

In the "Fastener Attachment" configuration of
35 FIGS. 9 and 10, the extending tail 98 is employed, as well as the strip 102 of the "hook" element 102 of a hook-and-loop fastener system. A strip 138 of

adhesively-backed "loop" material is attached to the seat back rear surface 136 in an appropriate position. The fastener elements 102 and 136 together secure the extending tail 98 and thus the bottom panel 66 comprising part of the support structure 82 to the seat back 132. In the "Fastener Attachment" configuration of FIGS. 9 and 10, the D-ring 88 and tether strap 90 are not employed. The support structure 80, more particularly the support element 74 thereof, is adjusted, so that the mirror and backing assembly 60 is positioned at an appropriate angle for viewing the infant 38 along the optical axis 54 as is diagrammed in FIG. 1.

While specific embodiments of the invention have been illustrated and described herein, it is realized that numerous modifications and changes will occur to those skilled in the art. It is therefore to be understood that the appended claims are intended to cover all such modifications and changes as fall within the true spirit and scope of the invention.

Claims

1. A viewing panel device having a plurality of attachment configurations for use in vehicles including a relatively rearwardly-positioned vehicle seat with a seat back having a top surface, and of a plurality
5 of possible vehicle configurations including in vehicles having a top tether anchorage point intended for attachment of the top tether of a forward-facing child safety seat, and in vehicles having a headrest positioned
10 over the vehicle seat back, said device comprising:

a generally vertical viewing panel having a front viewing surface and a rear surface;

a bottom panel attached to said viewing panel generally on said rear surface and on a lower portion
15 thereof, said bottom panel having a top surface and a bottom surface that contacts the seat back top surface;

a fastener element connected to the viewing panel on an upper portion thereof;

a diagonal support element that can extend
20 between said viewing panel rear surface at an upper end of said support element and said bottom panel top surface at a lower end of said support element, said support element being removably attachable to one of said viewing panel rear surface and said bottom panel top surface;

25 a tether strap extending from said bottom panel and terminating in a fastener that can be attached either to the top tether anchorage point in a vehicle so configured or to said fastener element when said tether strap is looped around the headrest in a vehicle so
30 configured.

2. The device of claim 1, wherein said front surface of said viewing panel comprises a mirror positionable for viewing an infant in a rear-facing child safety seat on the vehicle seat.

3. The device of claim 1, wherein said diagonal support element is adjustably attachable to said bottom panel top surface.

4. The device of claim 1, which is for use in further possible vehicle configurations including in vehicles in which the vehicle seat back has an accessible rear surface, and in vehicles wherein the vehicle seat is a rear seat and which have a rear shelf behind the seat back, wherein:

10 said bottom panel has an extending tail;
 said extending tail has a fastener element on the underside thereof for removably fastening to the vehicle seat rear surface in vehicles in which the vehicle seat rear surface is accessible; and

15 said extending tail can be tucked in between the vehicle seat back and the rear shelf for frictional engagement in vehicles configured with a rear shelf behind the seat back.

5. A viewing panel device for use in a vehicle including a relatively rearwardly-positioned vehicle seat with a seat back having a top surface, and including a top tether anchorage point intended for attachment of the top tether of a forward-facing child safety seat, said device comprising:

25 a generally vertical viewing panel having a front viewing surface and a rear surface;
 a support structure connected to said viewing panel generally on said rear surface thereof, said support structure including a portion that contacts the

30 seat back top surface; and
 a tether strap extending from said support structure and terminating in a fastener that attaches to the top tether anchorage point.

6. The device of claim 5, wherein said front surface of said viewing panel comprises a mirror positionable for viewing an infant in a rear-facing child safety seat on the vehicle seat.

5 7. The device of claim 5, wherein said support structure is adjustable.

8. The device of claim 5, where said tether strap is adjustable.

9. The device of claim 5, wherein said support
10 structure and said tether strap are adjustable.

10. The device of claim 5, wherein said support structure comprises:

 a bottom panel having a top surface and a
bottom surface that contacts the seat back top surface;
15 and

 a diagonal support element that extends between
said viewing panel rear surface at an upper end of said
support element and said bottom panel top surface at a
lower end of said support element.

20 11. A viewing panel device for use in a
vehicle including a relatively rearwardly-positioned
vehicle seat with a seat back having a top surface and a
headrest positioned thereover, said device comprising:

 a generally vertical viewing panel having a
25 front viewing surface and a rear surface;

 a bottom panel attached to said viewing panel
generally on said rear surface and on a lower portion
thereof; said bottom panel having a bottom surface that
contacts the seat back top surface;

30 a fastener element connected to the viewing
panel on an upper portion thereof; and

a tether strap extending from said bottom panel and terminating in a fastener that attaches to said fastener element when said tether strap is looped around the headrest.

5 12. The device of claim 11, wherein said front surface of said viewing panel comprises a mirror positionable for viewing an infant in a rear-facing child safety seat on the vehicle seat.

10 13. The device of claim 11, wherein said tether strap is adjustable.

14. A viewing panel device for use in a vehicle including a rear vehicle seat with a seat back having a top surface, and a rear shelf behind the seat back, said device comprising:

15 a generally vertical viewing panel having a front viewing surface and a rear surface; and

 a support structure connected to said viewing panel generally on said rear surface thereof, said support structure including a portion that contacts the seat back top surface and said support structure having an extending tail;

 whereby said extending tail can be tucked in between the vehicle seat back and the rear shelf for frictional engagement.

25 15. The device of claim 14, wherein said front surface of said viewing panel comprises a mirror positionable for viewing an infant in a rear-facing child safety seat on the vehicle seat.

30 16. The device of claim 14, wherein said diagonally-extending support is adjustable.

17. The device of claim 14, wherein said support structure comprises:

a bottom panel having a top surface and a bottom surface that contacts the seat back top surface;
5 and

a diagonal support element that extends between said viewing panel rear surface at an upper end of said support element and said bottom panel top surface at a lower end of said support element.

10 18. A viewing panel device for use in a vehicle including a relatively rearwardly-positioned vehicle seat with a seat back having a top surface and a rear surface, said device comprising:

a generally vertical viewing panel having a front viewing surface and a rear surface; and
15

a support structure connected to said viewing panel generally on said rear surface thereof, said support structure including a portion that contacts the seat back top surface and said support structure having
20 an extending tail;

said extending tail having a fastener element on the underside thereof for removably fastening to the vehicle seat rear surface.

19. The device of claim 18, wherein said front surface of said viewing panel comprises a mirror positionable for viewing an infant in a rear-facing child safety seat on the vehicle safety seat.
25

20. The device of claim 18 which further comprises a mating fastener element that is secured to the vehicle seat rear surface and positioned for engaging said fastener element on said extending tail.
30

21. The device of claim 18, wherein said support structure is adjustable.

22. The device of claim 18, wherein said support structure comprises:

a bottom panel having a top surface and a bottom surface that contacts the seat back top surface;

5 and

a diagonal support element that extends between said viewing panel rear surface at an upper end of said support element and said bottom panel top surface at a lower end of said support element.